



# 2011 JR. MINI RULES

**AGE LIMIT IN JR.MINI CLASS...12yrs – 15yrs young.  
(If a driver begins the season at 15 and turns 16  
during the season they will be allowed to finish.)**

## **BODY**

1. Two or four door sedan body with steel top. No front wheel drive. Station wagons are o.k. Production wheelbase limited to 102".
2. Cars must have complete frame. Cutting allowed over rear axle to mount rear shocks but must be reinforced.
3. Cars must have complete firewall separating driver from engine and also separating trunk area from driver's compartment.
4. All glass, chrome, and trim must be removed.
5. All flammable materials must be removed.
6. Fenders may be cut for tire clearance but must maintain a stock configuration.
7. All cars must have a minimum of two (2) hood pins or bolts to keep hood closed.
8. Back of hoods must be completely sealed off and must stay that way while car is in motion.
9. No angle or channel iron outside of car.
10. Plastic nosepieces and tailpieces are allowed. **Any skirting must contour with the body.**
11. Aluminum body patches ok. Top and deck lid should remain stock.
12. Removable inspection panel required on driver dash area.
13. Minimum weight after race with driver is 2300 lbs.
14. Fire Extinguisher must be in driver reach securely mounted
15. Body should be painted and lettered in good taste

## **ROLL CAGE**

1. All cars must have a minimum six (6) point roll cage. All cages should be at least 1-1/4" outside diameter x .095 wall steel tubing. (no welded corners) Roll cage around driver must have padding.
2. Drivers head must be at least 2" below top of cage.
3. All cars must have at least three (3) door bars on driver side, two (2) bars on grandstand side. Door bars must be a minimum 1-1/4" x .095 wall steel tubing. Door bars must be sufficiently gusseted and tied to the car at the bottom.
4. Any bracing inside of car is legal except under the fenders.
5. Seat must be mounted to the roll cage and be on the left side of the car.
6. No tube frame car
7. Minimum 3 front window bars in front of driver.

## **BUMPERS**

1. Front bumpers must be centered on frame rails and in its original location.
2. Front bumpers may be 1-1/2" o.d., no more than 8" overall in height from top to bottom.
3. Front bumpers must not extend more than 2" in front of any body part and be no wider than center of tire. Ends must bend back into the frame and be welded. No blunt or sharp edges and no channel iron.
4. May have two (2) radiator protection bars in front of radiator and behind bumper within the confines of body.
5. Rear bumper may wrap around rear quarter panel and must tie into frame behind rear tire.
6. Rear bumper may be 1-1/2" o.d. pipe or tubing **no taller than 12"**.
7. Stock bumpers are allowed.

## **NERF BARS**

1. Nerf bars must be flush with body. No blunt or sharp edges.
2. Nerf bars must be 1" x 2" rectangle or 1" square only.
3. Nerf bars are only allowed between wheels.

## **ENGINE**

1. In line four cylinder (carburetor type only) with a maximum displacement of 2399cc.
2. Engine must be in stock location.
3. No rotary engines or turbos.
4. No dual overhead cams.
5. Engine must use stock block, and head. Steel valves only.
6. Must use stock intake. May be machined to receive carburetor only.
7. Milling of head to increase compression allowed. No porting, polishing or port matching allowed. NO GRINDING INSIDE OF PORTS. Straight boring allowed for large valves. Cannot go past short side radius. Bore cannot be polished.
8. Carburetor must be un-altered Holley #4412 or 5200 series with a stock venture bore, stock throttle body, and stock booster location. May run stock OEM carburetor not to exceed 500cfm. No Weber or Mikuni carburetors.
9. Battery type ignition only. No magnetos, dual points, MSD boxes.
10. Any solid surface cam, valve springs, rockers, and lifters are allowed. NO ROLLER CAM. Adjustable cam gears OK
11. Stock exhaust or racing headers are allowed. Must run stamped IMCA 609 muffler.
12. Exhaust should exit under car.
13. Blocks must have engine numbers.
14. No Stokers \*\*\*\*\*
15. Must have stock O.E.M. UNALTERED crankshaft.
16. 1" Sight plug in the side of the oil pan with a clear line of sight to the crankshaft and rods.

## **DRIVE TRAIN**

1. Standard or automatic transmissions are allowed. Automatic transmissions must use OEM torque converter.
2. Transmissions must have at least two (2) forward gears and one (1) reverse.
3. Rear end must be locked.
4. Drive shafts may be altered or welded and painted white.
5. No dog clutches or multi-disc clutches. No couplers.
6. No Aluminum flywheels allowed, MUST USE STEEL FLYWHEEL

## **SUSPENSION**

1. Front and rear suspension must be stock type, but may be re-enforced. No welding springs solid. No wooden blocks in springs.
2. One shock per wheel.
3. No weight jacks allowed. If weight jacks exist they must be disabled.

## **TIRES AND WHEELS**

1. 8" max steel wheels only. Rim centers may be completely welded and may be reinforced.
2. Racing studs and lug nuts are recommended
3. D.O.T. Street tires ONLY. No racing tires.
4. No bead locks
5. No grooving of tires
6. Right rear mud plug allowed
7. No bleeder valves

## **RADIATOR**

1. Only one (1) radiator is allowed and must be centered in front of car.

## **BATTERY**

1. One (1) 12 volt automotive battery allowed per car.
2. The battery must be mounted to frame or cage.

## FUEL AND FUEL TANK

1. Racing Gas allowed. No additives.
2. Racing fuel cell is required.
3. Fuel cell must be mounted to frame or cage with a minimum of two (2) steel straps 2" x 1/8" thick 360 degrees around cell, or bolted to cell frame.
4. If fuel cell does not have aircraft style positive seal filler neck/cap system - a flapper, spring or ball type filler rollover valve is required.
5. Fuel cell must be 12" from either side of car and 12" from the rear of the car body.
6. Floor in trunk must have holes drilled in it to allow spilled fuel to drain.
7. **If electric fuel pump is used, an automatic oil pressure cut off switch is required.**

## BRAKES

1. All cars must have a minimum of two (2) working rear brakes. Four wheel brakes are recommended.
2. Adjustable brake control cannot be in driver reach.

## SEAT BELTS & SAFETY EQUIPMENT

1. Snell-rated SA95, SA2000 or SA2005 helmet **required**.
2. Roll bar padding **required** in driver compartment (Fire retardant recommended).
3. SFI-approved full fire suit **required**.
4. Fire retardant neck brace, gloves and shoes **required**.
5. **Recommended:** Fire retardant head sock, underwear, head and neck restraints.
6. Driver-side window net **required**, minimum 16"x 20" ribbon or mesh style, and must be mounted so latch is at top front of window.
7. Minimum three-inch wide five point safety belt assembly **required** (Y-type shoulder harness not allowed), must be mounted securely to roll cage, and recommended to be no more than one year old.
8. Kill switch **required** within easy reach of driver and must be clearly marked 'OFF' and 'ON'.
9. Fire Extinguisher **required** and must be in driver reach securely mounted.